



PETROTM OIL

LubenzAdd® 2015

HYDRAULIC OIL ADDITIVE

❖ **PRODUCT INTRODUCTION:**

LubenzAdd 2015 is formulated with anti-oxidant, anti-corrosion and anti-wear agents. The hydraulic oil blended with LubenzAdd 2015 possesses excellent antioxidant, anti-rusting and antiwear properties, it can longer the service life of oil and hydraulic system. It provides excellent Demulsibility in use.

❖ **RECOMMENDED DOSAGE:**

Anti-wear	0.4%
HLP Grade	0.6%

❖ **PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:**

PROPERTIES	TYPICAL VALUE
Appearance	Clear, yellow liquid
Density, gm/cm ³ at 29.5°C	0.958
Phosphorus ,wt %	4.3
Zinc ,wt%	4.2
Kinematic Viscosity,CST @ 40°C	100
Flash Point	180
Sulphur content,% wt	8.5

❖ **PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:**

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ **SAFETY AND HANDLING INFORMATION:**

For further information, please refer to relevant MSDS