



LubenzAdd® 2030

HYDRAULIC OIL ADDITIVE

❖ **PRODUCT INTRODUCTION:**

LubenzAdd 2030 is a premium quality anti-wear additive package on zinc phosphorus chemistry. This premium anti-wear is enriched with rust and oxidation inhibitor. It meets the Requirements of DIN 51524, part 2&3. It is also recommended to be used in hydraulic oils which need extreme pressure properties. It can longer the service life of the hydraulic System.It provides good water and air repellence.

❖ **RECOMMENDED DOSAGE:**

Anti-wear	0.4%
HLP Grade	0.6%
AW & EP	0.8%

❖ **PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:**

PROPERTIES	TYPICAL VALUE
Appearance	Clear, yellow liquid
Density,gm/cm ³ at 29.5 °C	0.958
Phosphorus %	4.3
Zinc , wt. %	4.8
Kinematic Viscosity,CST @40°C	100
Flash Point	180
Sulphur, wt. %	8.5

❖ **PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:**

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ **SAFETY AND HANDLING INFORMATION:**

For further information, please refer to relevant MSDS