



LubenzAdd® 4200

2-STROKE ENGINE OIL ADDITIVE PACKAGE

❖ **PRODUCT INTRODUCTION:**

LubenzAdd 4200 is recommended for making 2- stroke motorcycle oil having high thermal stability. Its low ash additive. This product is formulated with low base number detergent and dispersant. It has excellent detergency, lubricity and dispersancy. This product is suitable for blending FB and FC level air cooling two-stroke motor engine oils that conform to the standard JASO M345 FB and FC.

❖ **RECOMMENDED DOSAGE:**

APPLICATION	TREATING RATE (MASS %)
JASO FB	2.20%
JASO FC	3.50%

❖ **PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:**

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual Inspection	Brown Clear Liquid
Calcium Content, %wt.	ASTM D4951	1.4 %
Nitrogen	ASTM D3228	0.50 %
TBN, mg KOH/gm	ASTM D2896	40
Flash Point	ASTM D92	Min 176

❖ **PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:**

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ **SAFETY AND HANDLING INFORMATION:**

For further information, please refer to relevant MSDS