



## **LubenzAdd® 6150**

### **AUTOMATIC TRANSMISSION FLUID ADDITIVE**

❖ **PRODUCT INTRODUCTION:**

LubenzAdd 6150 is versatile additive package that offers ability to easily formulate high performance of automatic transmission fluids using wide range of base stocks.

❖ **RECOMMENDED DOSAGE:**

PERFORMANCE	TREATING RATE (MASS%)
Dexron II D	5.70 %
Dexron III	10.20 %

❖ **PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:**

PROPERTIES	TEST METHOD	TYPICAL VALUES
<b>Appearance</b>	Visual Inspection	Dark Brown Clear Liquid
<b>Phosphorus %</b>	ASTM D4951	1.30 %
<b>Nitrogen %</b>	ASTM D5291	0.40 %
<b>Flash Point</b>	ASTM D92	Min 150

❖ **PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:**

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ **SAFETY AND HANDLING INFORMATION:**

For further information, please refer to relevant MSDS