



LubenzAdd® 6152 AUTOMATIC TRANSMISSION FLUID ADDITIVE

❖ PRODUCT INTRODUCTION:

LubenzAdd 6152 is suitable to prepare automatic transmission fluid for multi-vehicle meeting following specifications.

❖ RECOMMENDED DOSAGE:

PERFORMANCE	TREATING RATE (MASS%)
Alison C-4	4.20 %
Dexron III D	10.30 %
General Motor type suffix A (TASA)	4.20 %

❖ PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual Inspection	Dark Brown Clear Liquid
Phosphorus % wt	ASTM D4951	0.50 %
Nitrogen % wt	ASTM D3228	0.90%
Calcium content % wt	ASTM D4951	1.50 %
Zinc Content % wt	ASTM D4951	0.60 %
Flash Point	ASTM D92	Min 150
Kinematic Viscosity @ 100°C	ASTM D445	150

❖ PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ SAFETY AND HANDLING INFORMATION:

For further information, please refer to relevant MSDS