



LubenzAdd® 8020

PASSENGER CAR MOTOR OIL ADDITIVE

❖ PRODUCT INTRODUCTION:

LubenzAdd 8021 is a multipurpose additive designed to meet API SL/CF, SM, SN Crankcase oil. It is enriched with high temperature detergency and is capable to provide lubricity, despersancy, anti-wear and keep engine clean.

API	SAE VISCOSITY GRADE	TREAT RATE.
SL/CF	15W40 , 20W50	5.20%
SM	5W20, 5W30,10W30	6.00%
SN	5W20,5W30,10W30	6.60 %

❖ PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual Inspection	Dark Brown Clear Liquid
Nitrogen, %w/w	ASTM D3228	0.3
Zinc, %w/w	ASTDM 4951	1.0
Molybdenum, %w/w	ASTDM D4951	0.01
Phosphorus, %w/w	ASTDM D4951	0.8
Magnesium, %w/w	ASTDM D4951	0.9
TBN, mg KOH/gm	ASTDM 4951	100 – 110
Kinematic Viscosity in cst@100°C	ASTM D445	50 - 60
Flash Point	ASTM D92	Min 150

❖ PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

❖ SAFETY AND HANDLING INFORMATION:

For further information, please refer to relevant MSDS