



## LubenzAdd® 2050 Compressor Oil Additive

### ❖ **PRODUCT INTRODUCTION:**

LubenzAdd 2050 is an ashless concentrate package for the composition of especially designed rotary screw compressors where air discharge temperature is very high. It provides excellent dispersion, corrosion inhibition and oxidation inhibition.

### ❖ **RECOMMENDED DOSAGE:**

5% to 10%

### ❖ **Features:**

1. Ashless, free from heavy metals.
2. Outstanding oxidation inhibition results into longer service life.
3. Excellent corrosion protection to Ferrous and Non – Ferrous metal parts.
4. Release air fast.
5. Compatible with mineral base oil as well as Poly Alpha Olefins.

### ❖ **PRODUCT QUALITY CHARACTERISTICS & TEST METHOD:**

SR.NO	Parameter	Value
1	Appearance	Bright and Clear
2	Total base no, mg KOH/gm.	30
3	Density at 29.5°C	0.94
4	Viscosity, cSt at 40°C	120
5	Copper corrosion at 100Deg C for 3hrs	1a
6	Flash Point	240

### ❖ **PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:**

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

### ❖ **SAFETY AND HANDLING INFORMATION:**

For further information, please refer to relevant MSDS