



## LubenzAdd<sup>®</sup> 410 POUR POINT DEPRESSANT

### ❖ PRODUCT INTRODUCTION:

LubenzAdd 410 is Pour Point Depressant with excellent pour point depressing and shear stability suitable for group 1 and 2 base oil with medium and low viscosity.

### ❖ PRODUCT QUALITY CHARACTERISTICS:

PROPERTIES	TEST METHOD	TYPICAL VALUES
Appearance	Visual Inspection	Organic Viscous Liquid
Color	Visual Inspection	Yellow to Amber.
Specific Gravity at 25 °C	ASTM D 4052	0.860-0.900
Kinematic Viscosity @ 100°C., cst	ASTM D 445	100.0 Min
Flash Point, °C. COC	ASTM D 92	120.0 min

POUR POINT DEPRESSION IN SN 150	
<b>0.05%</b>	6 <sup>0</sup> C
<b>0.2%</b>	18 <sup>0</sup> C
<b>0.25%</b>	21 <sup>0</sup> C
<b>0.3%</b>	24 <sup>0</sup> C

### ❖ PRODUCT STORAGE / HANDLING / TRANSPORTATION / PACKAGE:

The Storage temperature should not exceed 50°C the loading / unloading and blending temperature should not exceed 60°C. It is not flammable, not explosive, not corrosive, in the items of safety, environment protection etc. it is normal petroleum product, with no special protection. The product packed with 200 Kgs drums and 50 kgs carbos.

### ❖ SAFETY AND HANDLING INFORMATION:

For further information, please refer to relevant MSDS.